

MODEL : LP800-C(800W)

Parameter		Specifications					
Operating range(@0°C ~ 40°C)	Voltage	3~500V					
	Current	0~20A					
	Max Power	800W at 40°C (derated to 608W at 55°C)					
MODE SPECIFICATIONS							
CC MODE	RANGE	HIGH_0~20A					
		LOW_0~2A					
	RESOLUTION	L:10mA :H100mA					
CV MODE	Accuracy	±0.1%±200mA (after 30sec wait)					
	RANGE	3~500V					
	RESOLUTION	100mV(remote sense) or 400mV(local sense)					
CR MODE	Accuracy	±0.1%±500mV					
	RANGE	HIGH_10~40kΩ					
		MID_1~4kΩ					
DYNAMIC MODE	RANGE	LOW_0.4~25Ω					
	Accuracy	HIGH&MID_±0.3%±8mΩ (with ≥6V at input)					
		LOW_±0.8%±8mΩ (with ≥6A at input)					
PROTECTION							
OVP		520V					
OPP		920W					
OTP		105°C(Heatsink Temp)					
Short & Open	Short	50mΩ(max), 70mΩ(typical)					
	Open	≥50kΩ					
Ripple & Noise	Current	2mA(rms)/20mA(p-p)					
	Voltage	100mV(rms)					
SLEW RATE (typical values: 5%~95%)							
	Current Slew Rate (Conditions: 3~500V)			Voltage Slew Rate		Resistance Slew Rate	
	High Range Step	Low Range Step	Transition Time	Voltage Step	Transition Time		
1	0.32A/ms	32A/s	8.0ms	4V/ms	8.0ms	(High & Middle Ranges = Current Slew Rate)	
2	0.8A/ms	80A/s	3.2ms	10V/ms	3.2ms		
3	1.6A/ms	160A/s	1.6ms	20V/ms	1.6ms		
4	3.2A/ms	0.32A/ms	800μs	40V/ms	800μs		
5	8A/ms	0.8A/ms	320μs	100V/ms	320μs		
6	16A/ms	1.6A/ms	160μs	200V/ms	160μs		
7	32A/ms	3.2A/ms	80μs	0.4V/μs	100μs		
8	80A/ms	8A/ms	32μs	1V/μs	100μs		
9	0.16A/μs	16A/ms	16μs	2V/μs	100μs		
10	0.32/μs	32A/ms	16μs				
Remote Sensing	5Vdc between sense And load input						
INPUT AC	220V ± 10% 50~60Hz/250mA						
Remote Interface	RS-232C & RS-485 & USB						
Cooling	Isolation DC FAN						
Dimensions (19-inch 3U Standard)	426mm(W) * 133mm(H) * 470mm(D) (630~840W)						
Weight	15kg(Net weight) / 16kg(Gross weight)						